11009-22.JVD.319544

## IN THE CLAIMS

Please amend claims 20 and 35 as follows.

Please enter new claims 41-43 as indicated below.

1-19 (canceled)

20 (currently amended) A rotary die cutting apparatus for cutting a moving web of

material having first and second opposing faces into blanks, said apparatus comprising:

a pair of cylinders in peripheral contact;

a rotary die mounted to one of said cylinders, said rotary die having cutting elements thereon adapted to <u>pierce both first and second faces and</u> generate blanks and scrap portions

from the moving web of material;

means for gripping scrap portions, said gripping means extending from said rotary die, said

gripping means registering with at least some of said scrap portions as said die rotates, said

gripping means sized and positioned so as [ not to pierce completely through said some portions-]

to pierce through the first face of the moving web and not to pierce through the second face

of the moving web; and

a stripping knife having an edge for contacting said scrap portions as said scrap portions are

stripped away from said gripping means.

RESPONSE TO OFFICE ACTION Attorney Docket No. 11009-22

Page 5 of 17

·JUN/06/2005/MON 05:52 PM WOODARD EMHARDT FAX No. 317 637 7561

P. 011

11009-22.JVD.319544

21. (previously presented) The apparatus of claim 20 wherein each said pair of

cylinders have co-acting cutting elements thereon.

22. (previously presented) The apparatus of claim 21 wherein said gripping means

has a top surface that does not extend above said cutting elements.

23. (previously presented) The apparatus of claim 20 wherein said gripping means is

integrally formed with said rotary die.

24. (previously presented) The apparatus of claim 20 wherein said gripping means

includes a plurality of projections arranged in a pattern of isosceles triangles.

25. (previously presented) The apparatus of claim 24 wherein said a plurality of

projections are approximately equally spaced apart.

26. (previously presented) The apparatus of claim 24 wherein for a web material

having a thickness of about .010 inches said projections have a height of about .015 inches.

27. (previously presented) The apparatus of claim 24 wherein said projections are

spaced together within a range of from about 25 to about 400 projections per square inch.

RESPONSE TO OFFICE ACTION Attorney Docket No. 11009-22

-JUN/06/2005/MON 05:52 PM WOODARD EMHARDT

FAX No. 317 637 7561

P. 012

11009-22.JVD.319544

28. (previously presented) A rotary die cutting apparatus for cutting a moving web of

material into blanks, said apparatus comprising:

a pair of cylinders in peripheral contact;

a rotary die removably mounted to one of said cylinders, at least one of said rotary dies

having a cutting element thereon adapted to generate blanks and scrap portions from the moving

web of material, the outer edge of said cutting element being located a first distance from the

centerline of the one said cylinder;

a plurality of gripping elements extending from the one said cylinder, said gripping

elements registering with at least some of said scrap portions as said cylinders rotate, said

gripping elements sized and positioned so as not to pierce completely through said scrap

portions, each said gripping element having a tip located from the centerline of the one said

cylinder by a distance less than the first distance; and

a stripping knife having an edge for contacting said scrap portions as said scrap portions

are stripped away from said gripping elements.

29. (previously presented) The apparatus of claim 28 wherein each said pair of

cylinders have co-acting cutting elements thereon.

30. (previously presented) The apparatus of claim 28 wherein said gripping elements

are integrally formed with one of said rotary dies using one of the methods of electrical discharge

machining, photo-etching, and chemical etching.

RESPONSE TO OFFICE ACTION
Attorney Docket No. 11009-22

Page 7 of 17

11009-22.JVD.319544

(previously presented) The apparatus of claim 28 wherein said gripping elements 31.

are arranged in a pattern of isosceles triangles.

(previously presented) The apparatus of claim 31 wherein said gripping elements 32.

are approximately equally spaced apart.

33. (previously presented) The apparatus of claim 28 wherein for a web material

having a thickness of about .010 inches said gripping elements have a height of about .015

inches.

34. (previously presented) The apparatus of claim 33 wherein said gripping elements

are spaced together within a range of from about 25 to about 400 gripping elements per square

inch.

(currently amended) A rotary die cutting apparatus for cutting a moving web of 35.

material into blanks, said apparatus comprising:

a pair of cylinders in peripheral contact;

a rotary die mounted to one of said cylinders, said rotary die having cutting elements

thereon adapted to generate blanks and scrap portions from the moving web of material;

a plurality of gripping elements extending from the one said cylinder, said gripping

elements registering with at least some of said scrap portions as said cylinders rotate, said

RESPONSE TO OFFICE ACTION Attorney Docket No. 11009-22

·JUN/06/2005/MON 05:52 PM WOODARD EMHARDT

FAX No. 317 637 7561

P. 014

11009-22.JVD.319544

gripping elements sized and positioned so as [ not to pierce completely ] to partially pierce

through the thickness of said scrap portions, each said gripping element being integral with each

other said gripping element[,]; and

a stripping knife having an edge for contacting the leading edges of said scrap portions as

said scrap portions are stripped away from said gripping elements.

36. (previously presented) The apparatus of claim 35 wherein each said pair of

cylinders have co-acting cutting elements thereon.

37. (previously presented) The apparatus of claim 35 wherein said gripping elements

are fabricated integrally using one of the methods of electrical discharge machining, photo-

etching, and chemical etching.

38. (previously presented) The apparatus of claim 37 wherein said gripping elements

are arranged in a pattern of isosceles triangles.

39. (previously presented) The apparatus of claim 37 wherein said gripping elements

have a height of about .015 inches.

RESPONSE TO OFFICE ACTION Attorney Docket No. 11009-22 11009-22.JVD.319544

40. (previously presented) The apparatus of claim 37 wherein said gripping elements are spaced together within a range of from about 25 to about 400 gripping elements per square inch.

41. (new) The rotary die cutting apparatus of claim 20 wherein said gripping means includes a plurality of gripping elements having the shape of truncated cones having an undercut upper portion.

42. (new) The rotary die cutting apparatus of claim 28 wherein said gripping means includes a plurality of gripping elements having the shape of truncated cones having an undercut upper portion.

43. (new) The rotary die cutting apparatus of claim 35 wherein said gripping means includes a plurality of gripping elements having the shape of truncated cones having an undercut upper portion.

RESPONSE TO OFFICE ACTION Attorney Docket No. 11009-22 Page 10 of 17